ROMANO
Indoor & Outdoor Solutions

SPEC SHEET

BOSCH / BUILT-IN OVEN

Series 6 Pyrolytic Built-in Double Oven



RANGE
Series 6
TYPE
Built-in oven
WIDTH
60 cm
FUEL
Electric
CAPACITY
71 L + 34 L
FINISHES
Stainless steel
CODE
MBG578FS3A

WARRANTY (DOMESTIC USE)

Manufacturer's warranty: 2 years

Conditions: domestic use; proof of purchase; bought and used in Australia. Summary of the Bosch warranty terms and conditions, checked 7 November 2026. Full terms from Romano or the brand.

FEATURES

- Two ovens in one 888mm tall unit
- Pyrolytic self-cleaning
- 30 automatic programmes (AutoPilot 30)
- Meat probe
- 3D Hotair on up to three levels

DIMENSIONS

The dimension drawing and full specifications from Bosch follow on the next page.

Series 6, Built-in double oven, Stainless steel
MBG578FS3A



- **Pyrolytic self-cleaning**: Less cleaning effort thanks to automatic self-cleaning.
- **3D Hotair**: Even heat distribution for perfect results on up to three levels.
- **AutoPilot 30**: Perfect results with 30 pre-set automatic programmes.
- **Meat Probe**: Measures the optimal core temperature for perfectly cooked results.
- **Cool-touch door**: Insulation keeps exterior cooler to the touch for added comfort and confidence.

Color / Material Front: ..... Stainless steel
Built-in / Free-standing: ..... Built-in
Cleaning system: ..... Pyrolytic
Dimensions (HxWxD): ..... 888x594x550 mm
Dimensions of the packed product (HxWxD): .....960x660x690 mm
Control Panel Material: ..... Stainless steel
Door Material: ..... Glass
Net weight: .....59.5 kg
Usable volume of cavity: ..... 71 l
Heating functions: .... Defrost, Full width grill, Hot air gentle, Hot Air, Conventional heat, Pizza setting, Low temperature cooking, Bottom heat, Hot Air grilling, Warming
EAN code: 4242005465859
Energy efficiency rating: .....A
Energy consumption per cycle conventional (2010/30/EC): ..... 1.02 kWh/cycle
Energy consumption per cycle forced air convection (2010/30/EC): 0.81 kWh/cycle
Energy efficiency class (2010/30/EC) - cavity 2: ..... B
Energy consumption per cycle conventional - cavity 2 (2010/30/EC): 0.83 kWh/cycle
Energy efficiency index (2010/30/EC): .....95.3 %
Energy efficiency index cavity 2 (2010/30/EC): ..... 120.3 %
Connection rating: ..... 6300 W
Fuse protection: .....32 A
Voltage: .....220-240 V
Frequency: ..... 50 Hz
Plug type: .....No plug (electrical connection by licensed electrician), fixed connection
Included accessories: 1 x combination grid, 1 x universal pan, 1 x air fry & grill tray

1 x combination grid, 1 x universal pan, 1 x air fry & grill tray

HEZ327000	Pizza stone
HEZ32WA00	Wireless food thermometer
HEZ530000	Half tray
HEZ531010	Baking tray, non-stick ceramic coated
HEZ532010	Universal pan, non-stick ceramic coated
HEZ538000	1fold telescopic rail, level independent
HEZ629070	Air Fry & Grill tray
HEZ631070	Baking tray, enamelled
HEZ634000	Baking and roasting grid
HEZ638000	Full ext rails, level independent

4 242005 465859

Pages from Bosch's own specification. Ask us about this product, we're happy to help.
Romano Indoor & Outdoor Solutions, 4/126 Canterbury Rd, Kilsyth South VIC 3137. 03 9720 4633. sales@romanoios.com.au

BOSCH

Series 6, Built-in double oven, Stainless steel MBG578FS3A

Heating Functions
- Temperature range 30 °C - 275 °C
- Cavity volume: 71 net usable litres

Racks and Rails
- Number of shelf levels: 5
- 1 level telescopic rail

Design
- Rotary control knobs, Retractable control knobs
- Cavity inner surface: enamel
- Extra large capacity oven

Cleaning
- Pyrolytic self-cleaning function
- Cleaning Assistance (manually)
- Full glass inner door

Convenience
- LCD-display control (white)
- Electronic clock/timer with end time programming
- Automatic temperature proposal, Automatic start, Actual temperature display, Meat probe function
- AutoPilot, 30 automatic programs
- Bottom hinged door
- Bar handle
- Oven door with SoftOpen and SoftClose door
- Automatic programs
- Automatic rapid heat function
- Halogen lighting
- Integrated cooling fan

Accessories
- 1 x air fry & grill tray, 1 x combination grid, 1 x universal pan

Safety Features
- Maximum door temperature 30° C
- Quadruple glazed CoolTouch door
- Electronic door lock, Child lock, Automatic safety switch off function, Residual heat indicator

Technical Information
- Nominal voltage: 220 - 240 V
- Total connected load electric: 6.3 KW

Dimensions
- Appliance dimensions (HxWxD): 888 mm x 594 mm x 550 mm
- Installation dimensions (HxWxD): 875 mm - 888 mm x 560 mm - 568 mm x 550 mm
- Please reference the built-in dimensions provided in the installation drawing
- We recommend you to choose complementary products within SER6, in order to assure an optimal design combination of your Built-In appliances.

Pages from Bosch's own specification. Ask us about this product, we're happy to help.
Romano Indoor & Outdoor Solutions, 4/126 Canterbury Rd, Kilsyth South VIC 3137. 03 9720 4633. sales@romanoios.com.au