ROMANO
Indoor & Outdoor Solutions

SPEC SHEET

BOSCH / RANGEHOOD

Series 8 86cm Integrated Rangehood



RANGE
Series 8
TYPE
Rangehood
WIDTH
86 cm
FINISHES
Black
CODE
DLN88PC60A

WARRANTY (DOMESTIC USE)

Manufacturer's warranty: 2 years

Conditions: domestic use; proof of purchase; bought and used in Australia. Summary of the Bosch warranty terms and conditions, checked 7 November 2026. Full terms from Romano or the brand.

FEATURES

- Hidden in the overhead cabinet
- Up to 820 m^3/h extraction in boost
- SilentPowerDrive motor
- Filter saturation indicator
- LED softlight lighting

DIMENSIONS

The dimension drawing and full specifications from Bosch follow on the next page.

BOSCH

Series 8, integrated rangehood, 86 cm, Black
DLN88PC60A



LED Light

The undermount rangehood offers you flexibility in your kitchen planning, all with sleek styling and excellent performance – now in a brand new black colour, matching modern kitchens with Induction, Ceramic, and black-glass Gas Cooktops.

- **SilentPowerDrive**: The quiet and powerful motor for rangehoods.
- **Seamless integration**: Thanks to near flush installation, the rangehood is almost invisible in upper cabinets.
- **Intensive speed with reset**: Clears strong odours, then automatically returns to normal.
- **Filter saturation indicator**: Automatic reminders to clean your metal grease filters.
- **LED lighting**: Energy-efficient, bright, even cooktop illumination.

DHZ5316	Standard odor filter (replacement)
DHZ5605	Standard recirculation kit

Typology:	Built-in/Built-under
Length electrical supply cord:	150 cm
Required niche size for installation (HxWxD):	345 x 836.0 x 264 mm
Height of the chimney:	GENERAL.N_A mm
Minimum distance above an electric cooktop:	600 mm
Minimum distance above a gas cooktop:	650 mm
Net weight:	9.2 kg
Type of control:	Electronic
Number of power settings:	3-stages + intensive setting
Max. air extraction:	595 m^3/h
Boost position output recirculating:	780 m^3/h
Max. air recirculation:	570 m^3/h
Boost position air extraction:	820 m^3/h
Number of lights:	2
Noise level:	61 dB(A) re 1 pW
Diameter of air outlet:	120 / 150 mm
Grease filter material:	Washable aluminium
EAN code:	4242005475681
Connection rating:	172 W
Fuse protection:	3 A
Voltage:	220-240 V
Frequency:	60; 50 Hz
Plug type:	Standard 10 Amp plug
Installation type:	Built-in

4 242005 475681

Pages from Bosch's own specification. Ask us about this product, we're happy to help.
Romano Indoor & Outdoor Solutions, 4/126 Canterbury Rd, Kilsyth South VIC 3137. 03 9720 4633. sales@romanoios.com.au

Series 8, integrated rangehood, 86 cm, Black
DLN88PC60A

The undermount rangehood offers you flexibility in your kitchen planning, all with sleek styling and excellent performance – now in a brand new black colour, matching modern kitchens with Induction, Ceramic, and black-glass Gas Cooktops.

Design:
- For installation in a kitchen cabinet
- Flush-fitted installation for a seamless integration in upper kitchen cabinets
- Suitable for ducted or recirculated extraction
- For recirculated extraction various recirculation kits are available as optional accessories.

Features:
- SilentPowerDrive: Efficient BLDC technology
- 2 x 1 Watt LED lights with color temperature selectable from 2 fixed values
- SoftLight: the lighting elements switch on and off smoothly.
- Dimming function: the brightness of the lighting elements can be adjusted.
- Colour Temperature: 4000 K
- Light Intensity: 250 lux
- 2 metal grease filter(s)

Comfort Features:
- Electronic controls with low-lift push buttons
- Saturation display for filters
- Automatic after running (10 minutes)
- 3 power settings plus intensive setting
- Automatic reset from intensive to normal setting after 6 min

Cleaning Comfort:
- Metal grease filter dishwasher-safe
- Easy to clean smooth surfaces and materials

Performance Exhaust:
- According to EN 61591 and EN/ IEC 60704-2-13 your appliance can achieve the following values in exhaust mode: Speed 1: extraction rate 270 m3/h; noise level 42 dB (A) re1pW Speed 2: extraction rate 395 m3/h; noise level 51 dB (A) re1pW Speed 3: extraction rate 595 m3/h; noise level 61 dB (A) re1pW Intensive 1: extraction rate 820 m3/h; noise level 68 dB (A) re1pW

Performance Recirculation:
- According to EN 61591 and EN/ IEC 60704-2-13 your appliance can achieve the following values in recirculation mode with standard recirculation kit (available as optional accessory):
- Speed 1: extraction rate 190 m3/h; noise level 56 dB(A) re1pW
- Speed 2: extraction rate 230 m3/h; noise level 63 dB(A) re1pW)
- Speed 3: extraction rate 360 m3/h ; noise level 70 dB(A) re1pW)
- Intensive Speed 1: extraction rate460 m3/h; noise level 75 dB (A) re1pW)

Technical Information:
- Consumption data:
- Power rating: 172 W
- Voltage: 220 - 240 V

Planning and Installation Information:
- Appliance dimensions (HxWxD): 345 x 860 x 282 mm
- Dimensions recirculating (HxWxD): 345-345 x 860 x 282 mm
- Installation dimensions (HxWxD): 345 x 836 x 264 mm
- Please reference the built-in dimensions provided in the installation drawings
- Electrical cable length 1.5 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- with one-way flap: prevents outside air from entering your kitchen

Pages from Bosch's own specification. Ask us about this product, we're happy to help.
Romano Indoor & Outdoor Solutions, 4/126 Canterbury Rd, Kilsyth South VIC 3137. 03 9720 4633. sales@romanoios.com.au