ROMANO
Indoor & Outdoor Solutions

SPEC SHEET

CLARK / KITCHEN SINK

Punch Mega Bowl Sink with Drainer



RANGE
Punch
TYPE
Kitchen sink
BOWLS
Single with drainer
MATERIAL
Stainless steel
TAP HOLES
One
FINISHES
Stainless steel
CODE
PU1211.1L

WARRANTY (DOMESTIC USE)

Stainless steel sink: Lifetime cover for replacement product or parts only; 1 year cover for labour

Conditions: Covers defects from faulty materials or workmanship only; Not covered: misuse, accidents, harsh conditions or repairs by anyone other than a licensed agent; Scratching and general surface wear from normal use are excluded from the finish cover. Summary of the Caroma Warranty Conditions, version 16, effective 1 April 2026 (PDF: cdn.caroma.com Update, checked 7 November 2026. Full terms from Romano or

FEATURES

- Oversized single bowl for family washing up
- Drainer, one tap hole, left hand bowl
- Includes stainless steel basket waste
- 304 grade stainless steel

DIMENSIONS

The dimension drawing and full specifications from Clark follow on the next page.

Cut here for template

CLARK

Punch Mega Bowl Sink

This pack contains the following components to assist in the installation of your product:
- Fixing Clips
- Sealing Tape
- 90mm Basket Waste

Suitable for item codes: PU1211.1L and PU1211.1R

INSTALLATION INSTRUCTIONS

1. Finish cutting out this template with a knife or scissors.
2. Position the template on the bench top and draw a pencil line against the edge of the template. Then check the size against the overall cutout dimensions before cutting the bench top.
3. Following the inside edge of the pencil line carefully cut out the hole in the bench top. An exact cut is required to obtain best fit.
4. For a normal thickness benchtop the enclosed fixing clips should be suitable. See Figure A. Lightly hammer the fixing clips onto the clip brackets at equal points along the product rim as shown in Figure B.
5. Position the product in the cut out hole so that it is properly aligned. Check that the sealing tape will seal evenly around the edge of the hole.
6. Remove the product and install the waste assemblies and the tap (if required). It is suggested that silicone sealer be used between the waste grate and hole.
7. Remove the protective backing from the sealing tape, apply a continuous bead of silicone sealer between the sealing tape and the edge of the product. Quickly place the product in position.
8. Close the fixing clip hinges as shown in Figure C.
9. Tighten the fixing clips evenly, using a low torque setting on any electric screw driver used. Overtightening may strip the thread.
10. Plumb up the tap and waste fittings.

GWA Bathrooms & Kitchens
Caroma Industries Limited
ABN 35 000 189 499
1 Melito Court, Prestons NSW 2170
National Customer Call Centre
13 14 16
caroma.com.au

New Zealand
National Customer Call Centre
09 279 2700
caroma.co.nz

Figure A




Figure B




Figure C



NOTE: For thin benchtops special clips (A0167) are available.

CUTOUT TEMPLATE DIMENSIONS - 1085 x 485mm

To use this cutout template for benchtops, print 1:1 on a large format printer

Corner radius 20mm

For installation guide print to fit on paper size.

PU1211_Rev 0